

UM220-IV NL

Industrial Grade Multi-GNSS
Navigation and Positioning Module



16.0 x 12.2 x 2.4 mm



Product Characteristics

- » Excellent navigation and positioning performance, supporting single-system standalone positioning and multi-system joint positioning
- » Anti-jamming design, which enables the module to work stably under complex electromagnetic environments
- » Low power consumption design
- » Hardware compatible with previous generation products and mainstream GPS modules
- » Supports NMEA V4.1 protocol
- » Surface Mount Device which facilitates users to produce

Applications



Vehicle
Navigation



Vehicle
Monitoring

Ordering Information

Supply at multiples of 500 pieces

Brief Introduction

UM220-IV NL is a multi-system GNSS module based on Unicore's proprietary low power high performance SoC - UFirebird. It supports AGNSS function, which improves the positioning speed with the help of assisted data transmitted through network. The module also supports high precision solution on the user's hardware platform to improve positioning accuracy. UM220-IV NL is of compact size and adopts SMT pad, supporting standard pick-and-place and fully automated integration of reflow soldering, particularly suitable for low cost and low power consumption applications.

13	GND	GND	12
14	NC	RF_IN	11
15	NC	GND	10
16	NC	VCC_RF	9
17	NC	NC	8
UM220-IV NL			
18	NC	RXD2	7
19	NC	TXD2	6
20	TXD1	GPIO2	5
21	RXD1	NC	4
22	V_BCKP	TIME PULSE	3
23	VCC	AADET_N	2
24	GND	nRESET	1

Physical Specifications

Dimensions	12.2 x 16.0 x 2.4 mm
Package	24 pin SMD
Weight	0.8 g
Temperature	Operating -40 °C ~ +85 °C Storage -45 °C ~ +90 °C

Electrical Specifications

Voltage	3.0 V ~ 3.6V DC
LNA	3.0 V ~ 3.3V, < 100 mA
Power Consumption ²	50 mW

Interfaces

2 x UART (LVTTL)
1 x 1PPS (LVTTL)

Functional Characteristics

AGNSS *

NOTE: * Supported by specific firmware
1 Open sky, using TruePoint RTK algorithm
2 Open sky, continuous tracking
3 Typical value, < 30m /s open sky
4 Open sky, continuous tracking

Performance Specifications

Channel	64 channels, based on UFirebird		
Frequency ¹	GPS L1 BDS B1 Galileo E1 QZSS		
Modes	Single-system standalone positioning or multi-system joint positioning		
Time to First Fix (TTFF) ¹	Cold Start: < 28 s Hot Start: < 1 s Reacquisition: < 1 s A-GNSS: < 4 s	Positioning Accuracy (CEP) ³	Horizontal: 2.0 m Vertical: 3.5 m
Data Update Rate	1 Hz	Velocity Accuracy(RMS) ³	0.1 m/s
1PPS	Support		
Sensitivity	GNSS		
	Tracking	-160 dBm	
	Cold Start	-147 dBm	
	Hot Start	-151 dBm	
	Reacquisition	-158 dBm	
Data Format	NMEA 0183, Unicore		